FE-4CIS-DVR

Standalone ATM DRV Datasheet

Key Features

- 5 channel (4 Analog Camera + 2 IP Camera) or 6 IP Camera
- Each channel supports up to Full HD (1080p), HD (720P) real-time recording
- Pre alarm recording: 5s, 10s, 15s, 20s, 25s, 30s, Max / canal
- Recovery system: auto reboot.
- On-screen display (OSD): 7 inch and Picture zoom support
- Embedded Linux OS
- Cooler system with 2-unit fan (heavy duty)
- User access (admin, user, guest), motion detection, image filter, water marking
- Network connection: TCP/IP, PPPOE, DHCP & DNS
- Log all the activities on NVR (NVR off, HDD format, logging & all alarm activity)
- Optional Modem 4G





Kategori	Parameter	Spesifikasi
Video/Audio Input	Video compression	H.264/H.265/H.265+
	Video input	4 x UTP Port + 1 IP Camera via Lan (RJ-45)
	Audio compression	Ogg Vorbis, 16Kbps
	Audio input	1-ch RCA (2.0Vp-p, 1KΩ)
	Display	2x2, 1+5, 1+7, 3x3
	Audio input interface	RCA (2.0Vp-p, 1KΩ)
	Voice talk input	1-ch , (Using Audio-In)
	Preview resolution	1280x1024, 1280x720, 1024x768, 800x800 + 1920x1080p (Ethernet)
Video/Audio Output	VGA output	1 VGA interface can support resolution: 1024x768/60Hz
	Recording resolution	1080p30, 1080p25, 720p60, 720p50, 720p30
	HDMI output	1 HDMI interface can support resolution: 1920x1080 ; 3840x2160
	Playback	Searching base on card number, search by time & channel
	Frame rate	PAL: 25 / NTSC: 30fps
	Stream type	Video/Video & Audio
	Support dual stream	Yes
	Bit rate	32Kbps~2Mbps, or user defined (Max 8Mbps)
	Audio output	1-ch, RCA (Linear, 1KΩ)
Hard Disk	Interface type	2 SATA Interface
	Capacity	Up to 10TB Capacity for Each Disk
External Interface	Communication interface	2 RJ45 10M/100M adaptive ethernet interface, 4 serial with RJ-45 Interface
	USB interface	2 USB interface, support USB disk, USB HDD, USB DVD-R/W and CD-R/W , Modem support (front panel)
	Alarm	input:8-ch, output:6-ch
	Input/Output control	8 input & 5 output digital/analog, 1 RS-485
	Support buzzer	Yes (camera tampering, HDD broken, Not recording, Serial cable lost & loss data TI)
General	Power supply	12VDC Consumption ≤10W (without HDD)
	Working temperature	-10°C - +55°C (14°F - 131°F) working humidity 10%-90%
	Dimension	135 x 200 x 180 mm
	Weight (without HDD)	≤5000g
	Serial monitoring	Serial monitoring able to combined with existing ATM monitoring
	ATM Feature	Time synchronize with host, Text Inserter, File naming with ATM ID, searching with unit number